FSF-25V936 -25℃ Medical Deep Freezer

FSF-25V936 (936L Medical Deep Freezer) is widely used in hospitals and laboratories. This is for placing and preserving storage such as drugs, vaccines, blood, enzymes, hormones, stem cells, extracted RNA and gene libraries and important biological and chemical reagents.



Features

- Fast pull down：Better cooling performance.
- Coil evaporator：Better temperature uniformity.
- Inner-door design：4 individual inner door.
- Universal castor wheels：Proven heavy-duty castors with brake.
- Lockable door：Standard lock with keys.
- Stainless steel materials：Antibacterial and corrosion resistant.
- Precise temp. Control：Temp. control accurate to 0.1℃.
- 7 types of alarm：Audible and visual alarms.
- USB Interface：10 years data for downloading.
- Eco-friendly：CFC-free refrigerant and energy-saving.

Structure

- High-precision probe
- Magnetic block
- Access port
- Castor with brake
- High-precision control system
- Inner door with built in handle
- Humanized handle with lock
- Heavy duty hinge
- Ambient temp alarm
- Sensor erro alarm
- High/low temp. Alarm
- Power failure alarm
- Door ajar alarm
- Thermostat failure alarm
- Abnormal voltage alarm

Technical Parameter

Performance		Refrigeration System		Alarms	
Cooling method	Direct Cooling	Refrigerant	R404a	High/low temperature	Y
Defrost	Manual	Temp. controller	Microprocessor	Power failure	Y
Shelf/drawer	Shelves/3	Sensor	NTC	Sensor error	Y
Temperature range	-10℃～-25℃	Display	Digital display	High ambient temperature	Y
Ambient temperature	10~32℃	External material	SPCC sprayed steel	Abnormal voltage	Y
Noise(db)	52	Internal material	Stainless Steel	Temperature controller malfunction	Y
Inner door Qty	4	Shelf material	Stainless Steel	Door ajar	Y
Access port QTY/Dia.	1/18mm	Compressor QTY	SECOP/2	Low battery	Y
				Power failure alarm(For controller)	72H

Electrical Data		Dimensions		Other	
Voltage frequency	220V 50/60Hz/or 110V/60Hz	Capacity(L/cu.ft)	936/33	USB Port	Optional
Power(W)	1000W	Exterior size(W*D*H)(mm)	1304×1000×2017	Remote alarm port	YES
Current(A)	5.8A	Interior size(W*D*H)(mm)	1000×700×1335	Data logger	Optional
Power consumption	10kWh/24h	Package size(W*D*H)(mm)	1370*1110*2200	Chart Recorder	Optional
		NW./GW.(kg)	340/376.5	RS485/232 port	Optional