Class B Pulsating Vacuum Desktop Autoclave (Automatic)

Features

- Error code to display the alarm and show the error information;
- Sterilization of surgical instruments, dental instruments, injection equipment and other medical devices that can with stand pressure steam;
- Durable 304 stainless steel electro-polished chamber made long lasting autoclave ,stainless steel door with mirror polish surface is highly resistance to corrosion;
- Open type top water tank designed to easily filling water and clean the tank;
- Safety door lock system,cycle will not start if the door is not locked.Door will not open at the end of cycle until chamber pressure equalizes to room pressure;
- Circular support basket Maximization of space utilization three layer trays;
- With high quality built-in thermal printer for paper printouts.





Top embedded water tank | Easy drain valve | Built-in thermal printer | Resistance to corrosion

Technical Parameter

Model	FSF-12L	FSF-16L	FSF-18L	FSF-23L	FSF-29L
Sterilizing Chamber Volume	12L Φ200x360mm	16L Φ230x360mm	18L Φ246x350mm	23L Φ246x450mm	29L Φ250x600m
Working Temperature	121℃/134℃				
Temperature Accuracy	0.1℃				
Max.Vacuum Rate	80kPa				
Drying Time	0-20min				
Display	LCD				
Vacuum Drying Function	Yes				
Interface	Built-in Printer				
Data Storage	No				
Standard Function	Safety lock door system,Pressure & temperature overload protection,Water shortage alarm				
Standard Tray No.	3	3	3	3	3
Material of Tray	SUS304 Stainless Steel				
Exterial Size (mm)	580x440x400	580x440x400	580x440x400	680x440x400	820x440x400
Packing Size (mm)	670x500x450	670x500x450	670x500x450	760x500x450	950x580x520
N.W./G.W. (kg)	41/50	42/51	44/52	49/57	56/70