

LCD Digital Orbital Shaker

SK-O180-Pro

SK-O330-Pro

Description:

- Max. load capacity is 7.5kg(O330) and 2.5kg(O180) with platform
- Double LCDs for independent display of time and speed
- Used with a wide variety of accessories
- Maintenance-free brushless DC motor
- Over speed detection and protection
- Remote function provides PC control and data transmission



SK-O180-Pro



SK-O330-Pro



Parameter:

Specifications	SK-O180-Pro	SK-O330-Pro
Orbital diameter	4mm	10mm
Max. load capacity (with platform)	2.5kg	7.5kg
Motor type	Brushless DC motor	Brushless DC motor
Motor input power	28W	28W
Motor output power	15W	15W
Power	30W	30W
Time settings range	1min–19h59min	1min–19h59min
Speed range	100–800rpm	100–500rpm
Speed display	LCD	LCD
Timer display	LCD	LCD
Voltage	100–240V,50/60Hz	100–240V,50/60Hz
Protection class	IP21	IP21
Dimension [W×D×H]	300×340×100mm	370×420×100mm
Weight	8.1kg	13.5kg
Permissible ambient temperature and humidity	5–40°C 80%R.H	5–40°C 80%R.H
Data connector	RS232	RS232