Portable Pressure Steam Sterilizer

Production Introduces



- Fully stainless steel structure.
- Hand wheel type of quick-open door structure.
- Indicator light indicates working state.
- Double scale indication pressure gauge.
- Time range :0-60min.
- Automatically shut off with beep reminding after sterilization.
- Electric heated.
- Easy to operate,safe and reliable.

Technical Parameter

Model	Capacity	Working Pressure	Working Temp.	Temp. Range	Max.safety Pressure	Timer Range	Heat Average	Power	Packing Size(mm)	G.W/ N.W(kg)
FSF-18LDJ	18L	0.14-0.16 MPa	126℃	105-126℃	0.1065MPa	0-60min	≤±1℃	AC220V.50HZ /2KW	410*410*520	18/16
FSF-24LDJ	24L								410*410*630	20/18

Portable Pressure Steam Sterilizer

- **Electric or LPG heated**



Production Introduces

- Fully stainless steel structure.
- Electric or LPG heated.
- Double scale indication pressure gauge.
- Easy to operate , safe and reliable.

Technical Parameter

Model	Sterilizing Volume(mm)	Max.Working Pressure	Max.Working Temp.	Max.safety Pressure	Power	Packing Size(mm)	G.W/ N.W(kg)
FSF-18LM	18L Φ280*260	0.16MPa	126℃	0.16MPa	AC220V.50HZ /2KW	410*410*430	16/14
FSF-24LM	24L Φ280*390					410*410*550	17/15