

Thermostatic water bath

Characteristics:

- Cold-rolling steel spraying exterior.
- Stainless steel Inner tank and cover.
- Intelligent Temperature control instrument adopts PID control, dual digital display, with functions of timing of operation(0-9999min) fixed value operation, automatically stop、 realization of over-temperature alarm, power-off compensation、 power failure memory, error correction and Menu lock.

Main technical parameters:



Model	DK-98-(II)A 1hole	DK-98-(II)A 1 row /2holes	DK-98-(II)A 1 row/4holes	DK-98-(II)A 1 row/6holes	DK-98-(II)A 2 row /4holes	DK-98-(II)A 2 row/6holes	DK-98-(II)A 2 row/8holes
Voltage	200-240V/100-120V						
Power(W)	400	500	1000	1500	1000	1500	2000
Temmotion (°C)	±0.5						
Tem-range (°C)	Room Temp.+5~100°C						
Tem. Sensitivity (°C)	≤±1						
Displayerror (°C)	≤±2.5						
Chamber Size (mm)	168*168*120	325*168*120	653*168*120	945*168*120	325*325*120	480*325*120	635*325*120
Products Size (mm)	360*240*190	510*240*190	830*380*190	1100*250*215	510*380*190	670*380*190	830*380*190
Packing Size (mm)	400*320*235	555*320*230	865*320*235	1170*320*230	550*475*235	715*475*235	870*480*235
N.W.(KG)	3.3	5	7	12	6.5	8.6	9
G.W.(KG)	4.3	6.5	8	14	7.7	9.3	10