Vertical Steam Sterilizer-Bolt Digital Displayed Automatic Type

Production Introduces

- Bolt structure;
- High quality stainless steel material;
- Microcomputer automatic control, arbitrary set of sterilization parameters;
- Digital display and touch buttons,standard test interface;
- The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning;
- With stainless steel bucket or basket;
- Buzzer reminder after sterilization, automatic stop;
- Automatic cooling air, sterilization end automatic exhaust steam.



Technical Parameter

Model	FSF-35AB	FSF-50AB	FSF-75AB	FSF-100AB	FSF-120AB	FSF-150AB
Volume	35L	50L	75L	100L	120L	150L
Power	2.5KW	3.5KW	4.5KW	4.5KW	4.5KW	6.0KW
Voltage	AC220V/50HZ					
Design Pressure	0.25MPa					
Design Temperature	139℃					
Rated Working Pressure	0.22MPa					
Rated Working Temperature	134℃					
Sterilization Temperature Setting Range	116℃~134℃					
Sterilization Time Setting Range	4~120 min					
Chamber Volume	Φ300x500	Φ350x525	Φ400x625	Φ450x650	Φ450x760	Φ500x780
Bucket Dimension	Φ280x400	Φ330x460	Φ380x560	Φ420x540	Φ420x660	Φ470x720
Outer Dimension (mm)	400x400x860	480x480x960	525x525x1060	555x555x1080	555x599x1200	605x649x1210
Packing size (L x W x H)(mm)	550x500x1030	580x630x1100	630x680x1190	690x650x1230	690x650x1330	750x700x1370
Gross/net Weight	49kg/36kg	70kg/55kg	82kg/66kg	94kg/76kg	96kg/77kg	111kg/90kg
Basket Dimension (Option)	-	Φ320x240x2	Φ360x280x2	Φ410x300x2	Φ410x350x2	Φ460x350x2